

bonga®

SIDEWALLS

TECH SPECS

GENERAL:

Fabric material

Fabric characteristics

- Single coated 740 g/m² or double coated 560 g/m²
- Fire retardant M2 / B1
- Water column 10 000 mm (single coated) - 8000 mm (double coated)
- Tensile strength 1200 N / 5 cm (single coated) - 1000 N / 5 cm (double coated)
- Watertight PVC coating on the outside (single coated) or on the inside and outside (double coated)

Wooden poles

- UV-index: 8
- Zippers and buckles to roll side walls up
- Pinewood
- Sleeves to slide side keder into
- Pole cap to protect the canvas
- Steel bases with holes for anchoring with pegs and/or screws
- Eye bolts at the top of the poles for anchoring with straps

Aluminium profile

- Height: 2.75 m
- Diameter: 7 cm
- Anodised aluminium
- Sleeves to slide top keder into

Panoramic window

- Transparent 625 g/m² PVC
- Fire retardant M2
- Optimal UV-protection

BASE

3 x 2.75 m




Panoramic window

3 x 2.75 m



Closed

2 x 2.75 m



Panoramic window

2 x 2.75 m



Closed

EXTENSION

3 x 2.75 m




Panoramic window

3 x 2.75 m



Closed

2 x 2.75 m



Panoramic window

2 x 2.75 m



Closed

AVAILABLE COLOURS



Double coated



Single coated